


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification 5 :</b> A43B 7/28		<b>A1</b>	<b>(11) International Publication Number:</b> WO 94/08479 <b>(43) International Publication Date:</b> 28 April 1994 (28.04.94)
<b>(21) International Application Number:</b> PCT/EP93/02801 <b>(22) International Filing Date:</b> 12 October 1993 (12.10.93)		<b>(81) Designated States:</b> JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). <b>Published</b> <i>With international search report.</i>	
<b>(30) Priority data:</b> VE92U000029 15 October 1992 (15.10.92) IT			
<b>(71) Applicant (for all designated States except US):</b> HTM SPORT S.P.A. [IT/IT]; Devision Skiboot & Trekking, Via Nome di Maria, 1a, I-31010 Maser (IT).			
<b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> PRANDINA, Enzo [IT/IT]; Via Foresto Vecchio n.11, I-Asolo (IT).			
<b>(74) Agent:</b> SZASZ, Tibor; Tyroliaplatz 1, A-2320 Schwechat (AT).			
<b>(54) Title:</b> ANATOMICAL FOOT-BED AND A PROCEDURE FOR ITS ASSEMBLY			
<b>(57) Abstract</b> <p>This invention concerns an anatomical foot-bed, in particular for footwear for skis and a procedure for its assembly. Anatomical foot-beds are known comprising two thin sheets of a flexible material, for example leather, plastic, fabric, etc., bound together along the edges to form a space filled with a polyhydric alcohol and an isocyanate separated by a thin membrane. Since the two sheets have been obtained from flat layers and joined together, such known foot-beds, however, have the drawback that they do not adapt perfectly to the foot, especially in the heel region and the foot arch region, as the joint prevents the same sheets from adapting. According to the invention all these drawbacks are eliminated therein that a rigid preformed inner sole (1) to the top of which an impermeable membrane (2) is applied delimiting a space (3) accessible from the outside for the introduction of hardening material.</p>			



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NE	Niger
BE	Belgium	GN	Guinea	NL	Netherlands
BF	Burkina Faso	GR	Greece	NO	Norway
BG	Bulgaria	HU	Hungary	NZ	New Zealand
BJ	Benin	IE	Ireland	PL	Poland
BR	Brazil	IT	Italy	PT	Portugal
BY	Belarus	JP	Japan	RO	Romania
CA	Canada	KP	Democratic People's Republic of Korea	RU	Russian Federation
CF	Central African Republic	KR	Republic of Korea	SD	Sudan
CG	Congo	KZ	Kazakhstan	SE	Sweden
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovak Republic
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TC	Togo
CZ	Czech Republic	MG	Madagascar	UA	Ukraine
DE	Germany	ML	Mali	US	United States of America
DK	Denmark	MN	Mongolia	UZ	Uzbekistan
ES	Spain			VN	Viet Nam
FI	Finland				

Anatomical foot-bed and a procedure for its assembly

This invention concerns an anatomical foot-bed, in particular for footwear for skis and a procedure for its assembly.

Anatomical foot-beds are known comprising two thin sheets of a flexible material, for example leather, plastic, fabric, etc., bound together along the edges to form a space filled with a polyhydric alcohol and an isocyanate separated by a thin membrane.

At the moment of use the membrane is broken, causing the two components to be mixed so as to form a homogeneous mixture and, after having introduced the footbed inside the article of footwear, the foot is introduced and rests on the foot-bed until the mixture solidifies.

Since the two sheets have been obtained from flat layers and joined together, such known foot-beds, however, have the drawback that they do not adapt perfectly to the foot, especially in the heel region and the foot arch region, as the joint prevents the same sheets from adapting.

Other foot-beds are known which are obtained by modelling standard plates made in materials containing several components or by hot deformation of these plates. However, such known foot-beds also present other drawbacks and in particular:

- they require special equipment for their preparation;
- they must be adapted by hand, following the modelling stage, as the articles of footwear vary in surface area in relation to the area where the foot rests, according to the manufacturer;
- they are not completely reliable in that they are made outside the article of footwear, i.e. in an ambient free from restrictions.

According to the invention all these drawbacks and shortcomings are eliminated with an anatomical foot-bed in particular for footwear for skis, as described in claim 1.

- 2 -

This invention is described in more detail hereunder with reference to the attached table of drawings in which:  
figure 1 is a prospective view of an anatomical foot-bed according to the invention,  
figure 2 is a view of the cross section 11-11 of fig,1; and  
figure 3 is a view of the longitudinal section.

As can be seen from the figures, the anatomical foot-bed according to the invention comprises a pre-formed inner sole 1 made preferably in polyethylene, to the top of which an impermeable membrane 2 is attached which forms a cavity 3 with the inner sole 1 and which is covered by a hygienic cover 4. Also the pre-formed inner sole is covered on the bottom by a hygienic cover 5..

The pre-formed inner sole has a light restraining border 6 in the region of the foot arch and the heel.

The pre-formed inner sole is provided with a hole 7, which connects the outside and the cavity 3 formed by the pre-formed inner sole 1 and the membrane 2.

In addition the pre-formed inner sole is provided in its bottom surface with several small holes 8, preferably a number between 3 and 20, with a diameter between 0,5 and 2 mm, preferably 1,25 mm, the function of which will be explained hereinafter.

Lastly, the pre-formed inner sole is provided, in the region where the front part of the foot presses, with transverse stitching 9 which joins the top surface of the inner sole to the impermeable membrane 2.

Preparation of the foot-bed according to the invention is carried out as follows:

At the moment of use, a self-hardening substance, e.g. silicon 10, is introduced using special equipment through hole 7 and subsequently the hole is closed by means of self-adhesive plug 11.

In other cases a polyhydric alcohol and an isocyanate can be used as the self-hardening substance.

The foot-bed is then inserted into the article of footwear and the foot 12 is introduced on top of this to

- 3 -

model it according to the anatomical form of the foot until the material solidifies.

The amount of material to be injected into every single foot-bed, related to the different sizes, or groups of sizes of ski boots, comes to the values shown in the attached table.

TABLE

During the introduction of the foot into the article of footwear, the user adopts the position most suitable to leave the foot in a neutral state, i.e. not completely without load, but at the same time not loaded by the weight of the body. The best situation is preferably for the user to be seated.

At this stage, any air inside the cavity 3 can escape through holes 8, and the stitching 9 has the function of stopping the silicon from spreading towards the front area of the inner sole, so as to prevent the formation of ridges due to silicon accumulating in the spaces between the toes, ridges which with time may be uncomfortable for the user.

Once the desired shape has been reached, the foot is removed from the article of footwear and a certain period (5-10 minutes) is allowed to pass for the hardening stage to be fully completed.

Once the hardening stage has been completed, the silicon has a hardness between 30 and 40 Shore D.

From what has been said, it is clear that the anatomical foot-pad according to the invention offers numerous advantages and in particular:

- the foot rests evenly on the foot-bed, thanks to the silicon filling the pre-existing spaces between the anatomical foot-bed and the foot of the user;
- a high degree of comfort is provided as the foot-bed is shaped in the ambient in which it is used, and that is, inside the shell.

- 4 -

CLAIMS

1. Anatomical foot-bed in particular for footwear for skis, comprising a rigid preformed inner sole (1) to the top of which an impermeable membrane (2) is applied delimiting a space (3) accessible from the outside for the introduction of hardening material.
2. Foot-bed according to claim 1 wherein: the foot-bed comprises a hygienic cover (4) applied on top to the impermeable membrane (2).
3. Foot-bed according to claim 1 wherein: the hardening material comprises silicon and a catalyst.
4. Foot-bed according to claim 1 wherein: the hardening material comprises a polyhydric acid and an isocyanate.
5. Foot-bed according to claim 3 and 4 wherein the hardening material at the end of the hardening stage has a hardness of 30-40 Shore D.
6. Foot-bed according to claims from 1 to 5 wherein: the space (3) formed by the inner sole (1) and the impermeable membrane (2) is accessible from the outside by means of a hole (7), which can be closed by means of a plug (11).
7. Foot-bed according to claim 1 wherein: the pre-formed inner sole (1) has a retaining border (6) at least in the heel and foot arch regions.
8. Foot-bed according to claim 1 wherein: the foot-bed comprises several holes (8) for air to escape.
9. Foot-bed according to claim 8 wherein: the foot-bed comprises from 3 to 20 holes, preferably 16, with a diameter between 0,5 and 2 mm, preferably of 1,25 mm.
10. Foot-bed according to claim 1 wherein: the upper surface of the inner sole is transversally bound to the overlying impermeable membrane at the front end.
11. Foot-bed according to claim 10 wherein: the inner sole comprises in the front area, transversal stitching (9) which connects the upper surface of the inner sole to the impermeable membrane (2).
12. Procedure for assembly of an anatomical foot-bed, in particular for footwear for skis, according to claim 1 to 11

- 5 -

comprising a rigid pre-formed inner sole (1) to the top of which an impermeable membrane (2) is applied delimiting a space (3) accessible from the outside for the introduction of hardening material characterized by the fact that:

- at least one aperture (7) is made on said foot-bed in its bottom surface,
- the hardening material is inserted into said space,
- said aperture is closed,
- the foot-bed is inserted inside the article of footwear,
- the foot is introduced into the article of footwear,
- time is given for the hardening material to solidify,
- the foot is removed from the article of footwear.

Fig.1





Fig. 2






Fig.3

## INTERNATIONAL SEARCH REPORT

Intern. App. No.  
PCT/EP 93/02801A. CLASSIFICATION OF SUBJECT MATTER  
IPC 5 A43B7/28

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 5 A43B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	EP,A,0 559 022 (NORDICA S.P.A.) 8 September 1993	1,6,7, 10-12
X	DE,A,30 41 713 (THIEL) 9 June 1982	1,6-8,12
X	WO,A,91 08684 (ORTHOFEET INC.) 27 June 1991	1,6-8,12
X	DE,A,22 00 354 (HUMANIC SCHUH AG) 27 July 1972	1,6,7,12
Y	DE,A,34 05 964 (LUTZ ET AL.) 24 January 1985	1-3,6,12
Y	EP,A,0 085 657 (TRICARICO) 10 August 1983	1-3,6,12

 Further documents are listed in the continuation of box C. Patent family members are listed in annex.

## \* Special categories of cited documents :

- 'A' document defining the general state of the art which is not considered to be of particular relevance
- 'E' earlier document but published on or after the international filing date
- 'L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- 'O' document referring to an oral disclosure, use, exhibition or other means
- 'P' document published prior to the international filing date but later than the priority date claimed

- 'T' later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- 'X' document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- 'Y' document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- 'Z' document member of the same patent family

Date of the actual completion of the international search

20 January 1994

Date of mailing of the international search report

04-02- 1994

Name and mailing address of the ISA

European Patent Office, P.O. 5818 Patentam 2  
 NL - 2280 HV Rijswijk  
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
 Fax (+31-70) 340-3016

Authorized officer

Mathey, X

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

Internat	al Application No
PCT/EP 93/02801	

Patent document cited in search report	Publication date	Patent family member(s)			Publication date
EP-A-0559022	08-09-93	NONE			
DE-A-3041713	09-06-82	NONE			
WO-A-9108684	27-06-91	US-A-	5042100	27-08-91	
		AU-A-	6972191	18-07-91	
		EP-A-	0505459	30-09-92	
		US-A-	5095570	17-03-92	
DE-A-2200354	27-07-72	AT-A-	326526	10-12-75	
		CH-A-	540022	28-09-73	
		GB-A-	1324312	25-07-73	
DE-A-3405964	24-01-85	AU-A-	4063085	10-09-85	
		DE-A-	3437786	17-04-86	
		WO-A-	8503624	29-08-85	
		EP-A, B	0154170	11-09-85	
		EP-A-	0172202	26-02-86	
		JP-A-	61005808	11-01-86	
EP-A-0085657	10-08-83	NONE			